



## TECHNICAL DATA SHEET

**Product name:** HERA  
**Product type:** Precast concrete paver

### **Geometric characteristics**

**Dimensions (in.):** height x width x length (Dimensions include the joint spacer)  
**RECTANGLE:** 2 3/8 x 6 5/16 x 9 7/16 (60 x 160 x 240 mm)  
**SQUARE:** 2 3/8 x 6 5/16 x 6 5/16 (60 x 160 x 160 mm)

**Joint width:** 1/8 in. (3 mm)

**Approximate weight:**  
**RECTANGLE:** 11.1 lb (5.07 kg)  
**SQUARE:** 7.6 lb (3.44 kg)

**Dimensional tolerances<sup>1</sup>**  
**Length and width:**  $\pm 1/16$  in. (1.6 mm)  
**Height:**  $\pm 1/8$  in. (3.2 mm)

### **Physical characteristics<sup>1</sup>**

**Compressive strength:** 8000 psi (55 MPa) (min)

**Freeze-thaw durability**  
**Loss of mass after 50 cycles:** 1 % (max)

**Water absorption:** 5 % (max)

### **Americans with Disabilities Act (ADA)**

**Surface slip resistance<sup>2</sup>:** slip-resistant surface texture

**Surface opening<sup>3</sup>:** joint opening size, 1/8 in. (3 mm)

#### **Notes**

1. Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
2. Accessible paths shall be slip resistant. The above mentioned product is considered slip resistant and therefore complies with this ADA design guideline.
3. Accessible paths shall not allow the passage of a sphere greater than 1/2 in. (13 mm) in diameter. Paver's joint openings size complies with this ADA design guideline.

*To learn more about the textures and colors for this product, please contact our representatives.*

**CANADA** 5255, rue Albert-Millichamp, Saint-Hubert, QC J3Y 8Z8  
**USA** 852 Pennsylvania Avenue, Pen Argyl, PA 18072  
Telephone: 450 656-2992 / Toll free: 1 877 832-4625  
Fax: 450 656-1983  
[www.techo-bloc.com](http://www.techo-bloc.com)

July 2015