



## TECHNICAL DATA SHEET

**Product name:** INDUSTRIA PAVER

**Product type:** Precast concrete paver

### Geometric characteristics

**Dimensions (in.):** height x width x length (Dimensions include the joint spacer)

#### 200 Series

200 x 200: 3 15/16 x 7 7/8 x 7 7/8 (100 x 200 x 200 mm)

200 x 200: 3 15/16 x 7 7/8 x 15 3/4 (100 x 200 x 400 mm)

#### 300 Series

300 x 100: 3 15/16 x 11 13/16 x 3 15/16 (100 x 300 x 100 mm)

300 x 150: 3 15/16 x 11 13/16 x 5 7/8 (100 x 300 x 150 mm)

300 x 300: 3 15/16 x 11 13/16 x 11 13/16 (100 x 300 x 300 mm)

#### 600 Series

600 x 100: 3 15/16 x 23 5/8 x 3 15/16 (100 x 600 x 100 mm)

600 x 200: 3 15/16 x 23 5/8 x 7 7/8 (100 x 600 x 200 mm)

600 x 300: 3 15/16 x 23 5/8 x 11 13/16 (100 x 600 x 300 mm)

600 x 600: 3 15/16 x 23 5/8 x 23 5/8 (100 x 600 x 600 mm)

**Joint width:** 1/8 in. (3 mm)

### **Approximate weight:**

200 Series: Variable 19.4 to 38.8 lbs (8.80 to 17.60 kg)

300 Series: Variable 14.6 to 43.7 lbs (6.60 to 19.80 kg)

600 Series: Variable 29.1 to 174.6 lbs (13.2 to 79.2kg)

### **Dimensional tolerances<sup>1</sup>**

Length and width:  $\pm 1/16$  in. (1.6 mm)

Height:  $\pm 1/8$  in. (3.2 mm)

### **Physical characteristics<sup>1</sup>**

**Compressive strength:** 8000 psi (55 MPa) (min)

### **Freeze-thaw durability**

Loss of mass after 50 cycles: 1 % (max)

**Water absorption:** 5 % (max)

### **Americans with Disabilities Act (ADA)**

**Surface slip resistance<sup>2</sup>:** slip-resistant surface texture

**Surface opening<sup>3</sup>:** joint opening size, 1/8 in. (3 mm)

### Notes

1. Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
2. Accessible paths shall be slip resistant. The above mentioned product is considered slip resistant and therefore complies with this ADA design guideline.
3. Accessible paths shall not allow the passage of a sphere greater than 1/2 in. (13 mm) in diameter. Pavers joint openings filled with joint filler material comply with this ADA design guideline.

*To learn more about the textures and colors for this product, please contact our representatives.*

**CANADA** 5255, rue Albert-Millichamp, Saint-Hubert, QC J3Y 8Z8

**USA** 852 Pennsylvania Avenue, Pen Argyl, PA 18072

Telephone: 450 656-2992 / Toll free: 1 877 832-4625

Fax: 450 656-1983

www.techo-bloc.com

November 2015