



TECHNICAL DATA SHEET

Product name: LINEA
Product type: Precast concrete paver

Geometric characteristics

Dimensions (in.): height x width x length (Dimensions include the joint spacer)

Small rectangles

3 15/16 x 3 15/16 x 8 7/8 (100 x 100 x 225 mm)
3 15/16 x 3 15/16 x 12 13/16 (100 x 100 x 325 mm)
3 15/16 x 3 15/16 x 16 3/4 (100 x 100 x 425 mm)

Large rectangles

3 15/16 x 5 7/8 x 8 7/8 (100 x 150 x 225 mm)
3 15/16 x 5 7/8 x 12 13/16 (100 x 150 x 325 mm)
3 15/16 x 5 7/8 x 16 3/4 (100 x 150 x 425 mm)

Joint width: 1/8 in. (3 mm)

Approximate weight:

Small Rectangles: Variable 10.9 to 20.6 lbs (4.95 to 9.35 kg)
Large Rectangles: Variable 16.4 to 30.9 lbs (7.43 to 14.03 kg)

Dimensional tolerances¹

Length and width: $\pm 1/16$ in. (1.6 mm)
Height: $\pm 1/8$ in. (3.2 mm)

Physical characteristics¹

Compressive strength: 8000 psi (55 MPa) (min)

Freeze-thaw durability

Loss of mass after 50 cycles: 1 % (max)

Water absorption: 5 % (max)

Americans with Disabilities Act (ADA)

Surface slip resistance²: slip-resistant surface texture

Surface opening³: joint opening size, 1/8 in. (3 mm)

Notes

1. Meets and exceeds the requirements of the ASTM C 936 Standard Specification for Solid Concrete Interlocking Paving Units.
2. Accessible paths shall be slip resistant. The above mentioned product is considered slip resistant and therefore complies with this ADA design guideline.
3. Accessible paths shall not allow the passage of a sphere greater than 1/2 in. (13 mm) in diameter. Pavers joint openings filled with joint filler material comply with this ADA design guideline.

To learn more about the textures and colors for this product, please contact our representatives.