



TECHNICAL DATA SHEET

Product name: INDUSTRIA SLAB
Product type: Precast concrete slab

Geometric characteristics

Dimensions (in.): height x width x length (dimensions include the joint width)
2 3/8 x 23 5/8 x 23 5/8 (60 x 600 x 600 mm)

Joint width: 1/8 in. (3 mm)

Approximate weight: 108.4 lb (49.2 kg)

Dimensional tolerances¹

Length and width: -1.0 mm to +2.0 mm
Height: ± 3.0 mm
Warpage: ± 3.0 mm

Physical characteristics¹

Flexural strength: 650 psi (4.5 MPa) (min)

Freeze-thaw durability

Loss of mass after 28 cycles: 0.102 lb/ft² (500 g/m²) (max)
Loss of mass after 49 cycles: 0.246 lb/ft² (1200 g/m²) (max)

Americans with Disabilities Act (ADA)

Surface slip resistance²: slip-resistant surface texture

Surface opening³: joint opening size, 1/8 in. (3 mm)

Solar Reflectance

Color	Solar Reflectance	Solar Reflectance Index (SRI)
Grey	0.30	34
Greyed Nickel	0.32	35
Beige Cream	0.30	32

Notes

1. Meets and exceeds the requirements of the CSA A231.1 Precast concrete paving slabs standard.
2. Accessible paths shall be slip resistant. The above mentioned product is considered slip resistant and therefore complies with this ADA design guideline.
3. Accessible paths shall not allow the passage of a sphere greater than 1/2 in. (13 mm) in diameter. Paver's joint openings size complies with this ADA design guideline.

To learn more about the textures and colors for this product, please contact our representatives.

CANADA 5255, rue Albert-Millichamp, Saint-Hubert, QC J3Y 8Z8
USA 852 Pennsylvania Avenue, Pen Argyl, PA 18072
Telephone: 450 656-2992 / Toll free: 1 877 832-4625
Fax: 450 656-1983
www.techo-bloc.com

November 2015